



TURNING RADIUS = 28'-1"
CURB TO CURB = 28'-8"
WALL TO WALL = 32'-10"

----- CHASSIS -----

CHASSIS: KME PREDATOR MPD W/16" RR
CAB: 4 DOOR
ENGINE: CAT C7 330 HP
TRANSMISSION: ALLISON 3000 EVS
FRONT AXLE: 20,000#
REAR AXLE: 24,000#

----- PUMP -----

PUMP: HAILE QMAX-150 1500 GPM SINGLE STAGE
INTAKES
DRIVER SIDE: 6" & 2 1/2"
OFFICER SIDE: 6" & 2 1/2"
FRONT: 8"
REAR:
DISCHARGES:
DRIVER SIDE: (2) 2 1/2"
OFFICER SIDE: (1) 4" & (1) 2 1/2"
FRONT: (1) 1 1/2"
REAR: (1) 3" LH
DECK GUN: (3) 1 3/4" CROSSLAWS
OTHER:

----- TANK -----

TANK: FIBERGLASS
WATER: 600
FOAM: EXTRA FILLS:
DUMPS:

----- BODY -----

BODY TYPE: 139" FLATBACK
MATERIAL: 3/16" ALUMINUM
COMPARTMENTATION
DRIVER SIDE: FULL HEIGHT/SPLIT DEPTH
OFFICER SIDE: LOW
HOSEBED:
CAPACITY: 70 CU. FT.
DIVIDERS: ONE (1)
HOSE LOAD: 1,000' OF 4"
1,000' OF 2 1/2"

----- MISC. -----

GENERATOR: ONAN 6KW
FOAM SYSTEM: N/A

CUSTOMER APPROVAL:

NAME:
TITLE:
DATE:

THIS DRAWING IS A GENERAL CONFIGURATION AND MAY NOT NECESSARILY REFLECT ALL CONTRACTUAL REQUIREMENTS. CONTRACT SPECIFICATIONS SHALL PREVAIL OVER DRAWING

A	9-17-08	REVISED TO PRE CON	JGH
SYM	DATE	REVISION DESCRIPTION	APP'D

SALES ENGINEER : JASON HARTZ



KOVATCH MOBILE EQUIPMENT
ONE INDUSTRIAL COMPLEX - NORTHERNVA, VA 20240

DATE: 8-26-08
SCALE: 1"=24"
DWG SIZE/DRAWN BY: JIM
APPROVED BY: JGH

KME CUSTOM PUMPER

TRENTON FD, NJ

GSO#7396